

**Series 2, Integrated cooker hood, 60 cm, Silver
DEM66AC00B**



DWZOIM0A0 Standard odor filter (replacement)

B

Integrated cooker hoods pull out when in use and close neatly to conceal when not in operation.

- **LED Illumination:** The energy-saving lighting provides bright and clear lighting for the hob area.
- **3-speed power Level options to suit your cooking style and recipes.**
- **Ducted or Non-ducted Options**

Typology: Built-in/Built-under
 Length electrical supply cord: 150.0 cm
 Minimum distance above an electric hob: 500 mm
 Minimum distance above a gas hob: 650 mm
 Net weight: 10.8 kg
 Type of control: mechanical
 Number of speed settings: 3
 Max. air extraction: 625 m³/h
 Max. air recirculation: 416 m³/h
 Maximum Air flow: 625 m³/h
 Number of lights: 2
 Noise level: 70 dB(A) re 1pW
 Diameter of air outlet: 150 / 120 mm
 Grease filter material: Washable aluminium
 EAN code: 4242005041121
 Connection rating: 256 W
 Fuse protection: 10 A
 Voltage: 220-240 V
 Frequency: 50; 60 Hz
 Plug type: GB plug
 Installation typology: Wall-mounted



4 242005 041121

Series 2, Integrated cooker hood, 60 cm, Silver DEM66AC00B

Integrated cooker hoods pull out when in use and close neatly to conceal when not in operation.

Key performance features:

- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 max. 625 m³/h
- Noise max. Normal Level: Noise, max. speed in normal us: 70 dB dB*

Features

- Push button control for extractor speeds and light
- 3 power levels
- 2 x 3W LED
- Single motor
- 2 removable metal grease filter cassettes

Design

- Integrated hood
- Installation: Between Cupboards
- Push button control
- Mechanical

Performance/technical information

- Suitable for ducted or recirculating operation
- For recirculated extraction charcoal filter (accessory) needed
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 70 dB(A) re 1 pW
- Power rating: 256 W
- Light Intensity: 188 lux
- Colour Temperature: 2700 K
- Electrical cable length 1.5 m
- Blower Efficiency Class: B*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: C*
- Average Energy Consumption: 68.4 kWh/year*
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 402-402 x 599 x 271 mm
- Dimensions recirculating (HxWxD): 402-402 x 599 x 271 mm

Optional accessories

- Recirculating kit DWZ0IM0A0

* In accordance with the EU-Regulation No 65/2014

**Series 2, Integrated cooker hood, 60
cm, Silver
DEM66AC00B**

