

DA 2578

Extractor unit

with energy-efficient LED lighting and light-touch switches for easy use.



- Customised kitchen design – fully integrated in 702 mm width
- Unique user convenience – Con@ctivity
- Powerful – 600 m³/h in Booster level
- Efficient filtration- 10-ply stainless-steel grease filter
- Safe and easy to clean – Miele CleanCover



EAN: 4002515978276 / Material number: 10851350 /
Old Material Number: 28257855GB

General information	
Material number	10851350
EAN number	4002515978276
Construction type	
Integrated extractor	•
Operating modes	
Type of air guide	Can be retrofitted
Recirculation conversion kit (order separately)	DUU 151
Active charcoal filter (order separately)	DKF 15-P
Design	
Colour	Stainless steel
User convenience	
Miele@home	•
Automatic function Con@ctivity	•
Electronic controls	•
Controls	Light-touch switches with LEDs
Miele@mobile app	•
Power levels (number without Booster level)	3
Booster levels	1
Run-on time 5/15 min.	•
Grease filter saturation indicator	•
Active charcoal filter saturation indicator	•
Efficiency and sustainability	
Energy efficiency class (A+++ – D)	A
AC motor	•
Annual energy consumption in kWh/year	51.7
Fluid dynamic efficiency class	A
Lighting efficiency class	A
Grease filtering efficiency class	B
Cleaning and care	
Easy-to-clean canopy interior – CleanCover	•
Filter system	
Number of dishwasher-safe stainless steel grease filters (10-ply)	2
Lighting	
Number x W	2 x 3 W
Light intensity in lx	300 lx
Colour temperature in K	3000 Kelvin
Fan	
Dual-action blower	•
Exhaust air	
Air throughput in Level 1 (m ³ /h) according to EN 61591	250
Air throughput in Level 2 (m ³ /h) according to EN 61591	300
Air throughput in Level 3 (m ³ /h) according to EN 61591	360
Air throughput in Booster level 1 (m ³ /h) according to EN 61591	600
Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3	47.0

DA 2578

Extractor unit

with energy-efficient LED lighting and light-touch switches for easy use.



EAN: 4002515978276 / Material number: 10851350 /

Old Material Number: 28257855GB

Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3	51.0
--	------

Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3	56.0
--	------

Sound power in Booster level 1 (dB(A) re 1 pW) acc. to EN 60704-3	67.0
---	------

Sound pressure in Level 1 (dB(A) re 20 µPa) according to EN 60704-2-13	32.0
--	------

Sound pressure in Level 2 (dB(A) re 20 µPa) according to EN 60704-2-13	37.0
--	------

Sound pressure in Level 3 (dB(A) re 20 µPa) according to EN 60704-2-13	41.0
--	------

Sound pressure in Booster level 1 (dB(A) re 20 µPa) acc. to EN 60704-2-13	52.0
---	------

Recirculation

Air throughput in Level 1 (m³/h) according to EN 61591	200
--	-----

Air throughput in Level 2 (m³/h) according to EN 61591	250
--	-----

Air throughput in Level 3 (m³/h) according to EN 61591	320
--	-----

Air throughput in Booster level 1 (m³/h) according to EN 61591	530
--	-----

Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3	55.0
--	------

Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3	59.0
--	------

Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3	63.0
--	------

Sound power in Booster level 1 (dB(A) re 1 pW) acc. to EN 60704-3	72.0
---	------

Sound pressure in Level 2 (dB(A) re 20 µPa) according to EN 60704-2-13	44.0
--	------

Sound pressure in Level 3 (dB(A) re 20 µPa) according to EN 60704-2-13	48.0
--	------

Sound pressure in Booster level 1 (dB(A) re 20 µPa) acc. to EN 60704-2-13	57.0
---	------

Sound pressure in Level 1 (dB(A) re 20 µPa) according to EN 60704-2-13	39.0
--	------

Safety

Safety switch-off	•
-------------------	---

Technical data

Canopy width in mm	702
--------------------	-----

Canopy height in mm	50
---------------------	----

Canopy depth in mm	402
--------------------	-----

Net weight in kg	11.6
------------------	------

Length of supply lead in m	1.5
----------------------------	-----

Standard plug fitted	•
----------------------	---

Minimum height above electric hobs in mm	450
--	-----

Minimum safety distance above gas hobs (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm	650
--	-----

Number of phases	1
------------------	---

Total rated load in kW	0.22
------------------------	------

Voltage in V	230
--------------	-----

Fuse rating in A	10
------------------	----

DA 2578

Extractor unit

with energy-efficient LED lighting and light-touch switches for easy use.



EAN: 4002515978276 / Material number: 10851350 /
Old Material Number: 28257855GB

Frequency in Hz 50

Installation notes

Extraction ducting connection at top

•

Extraction ducting connection at rear

•

Diameter of exhaust duct in mm

150

Combination with WiFi-enabled Miele hob

recommended

Accessories included

Non-return flap

•