

DA 2628

Extractor unit

with energy-efficient LED lighting and light-touch switches for easy use.



- Customised kitchen design – fully integrated in 1180 mm width
- Unique user convenience – Con@ctivity
- Powerful – 640 m3/h in Booster level
- Energy-efficient and quiet – powerful ECO motor
- Elegant and efficient – edge extraction panels



EAN: 4002516001515 / Material number: 10851370 /
Old Material Number: 28262855GB

General information	
Material number	10851370
EAN number	4002516001515
Construction type	
Integrated extractor	•
Operating modes	
Type of air guide	Exhaust air
Design	
Colour	Stainless steel
Edge extraction	•
User convenience	
Miele@home	•
Automatic function Con@ctivity	•
Electronic controls	•
Controls	Light-touch switches with LEDs
Miele@mobile app	•
Power levels (number without Booster level)	3
Booster levels	1
Run-on time 5/15 min.	•
Grease filter saturation indicator	•
Efficiency and sustainability	
Energy efficiency class (A+++ – D)	A+
ECO motor	•
ECO motor (DC motor)	•
PowerManagement system	•
Annual energy consumption in kWh/year	26.8
Fluid dynamic efficiency class	A
Lighting efficiency class	A
Grease filtering efficiency class	A
Cleaning and care	
Easy-to-clean canopy interior – CleanCover	•
Filter system	
Number of dishwasher-safe stainless steel grease filters (10-ply)	4
Lighting	
Number x W	3 x 4,5 W
Light intensity in Lx	700 lx
Colour temperature in K	3500 Kelvin
Dimmer function	•
Fan	
Dual-action blower	•
Exhaust air	
Air throughput in Level 1 (m ³ /h) according to EN 61591	200
Air throughput in Level 2 (m ³ /h) according to EN 61591	300
Air throughput in Level 3 (m ³ /h) according to EN 61591	400
Air throughput in Booster level 1 (m ³ /h) according to EN 61591	640

DA 2628

Extractor unit

with energy-efficient LED lighting and light-touch switches for easy use.

EAN: 4002516001515 / Material number: 10851370 /
Old Material Number: 28262855GB

Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3 36.0

Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3 44.0

Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3 51.0

Sound power in Booster level 1 (dB(A) re 1 pW) acc. to EN 60704-3 62.0

Sound pressure in Level 1 (dB(A) re 20 µPa) according to EN 60704-2-13 22.0

Sound pressure in Level 2 (dB(A) re 20 µPa) according to EN 60704-2-13 30.0

Sound pressure in Level 3 (dB(A) re 20 µPa) according to EN 60704-2-13 37.0

Sound pressure in Booster level 1 (dB(A) re 20 µPa) acc. to EN 60704-2-13 48.0

Safety

Safety switch-off •

Technical data

Canopy width in mm 1180

Canopy height in mm 63

Canopy depth in mm 293

Net weight in kg 15.0

Length of supply lead in m 1.5

Standard plug fitted •

Minimum height above electric hobs in mm 450

Minimum safety distance above gas hobs (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm 650

Number of phases 1

Total rated load in kW 0.09

Voltage in V 230

Fuse rating in A 10

Frequency in Hz 50

Installation notes

Extraction ducting connection at top •

Extraction ducting connection at rear •

Diameter of exhaust duct in mm 150

Combination with WiFi-enabled Miele hob recommended

Accessories included

Non-return flap •