

DA 2698

Extractor unit

with energy-efficient LED lighting and light-touch switches for easy use.



- Customised kitchen design – fully integrated in 880 mm width
- Unique user convenience – Con@ctivity
- Powerful – 640 m³/h in Booster level
- Energy-efficient and quiet – powerful ECO motor
- Elegant and efficient – edge extraction panels



EAN: 4002516001492 / Material number: 10851400 /
Old Material Number: 28269855GB

General information	
Material number	10851400
EAN number	4002516001492
Construction type	
Integrated extractor	•
Operating modes	
Type of air guide	Can be retrofitted
Recirculation conversion kit (order separately)	DUU 151
Active charcoal filter (order separately)	DKF 19-P
Design	
Colour	Stainless steel
Edge extraction	•
User convenience	
Miele@home	•
Automatic function Con@ctivity	•
Electronic controls	•
Controls	Light-touch switches with LEDs
Miele@mobile app	•
Power levels (number without Booster level)	3
Booster levels	1
Run-on time 5/15 min.	•
Grease filter saturation indicator	•
Active charcoal filter saturation indicator	•
Efficiency and sustainability	
Energy efficiency class (A+++ – D)	A+
ECO motor	•
ECO motor (DC motor)	•
PowerManagement system	•
Annual energy consumption in kWh/year	28.6
Fluid dynamic efficiency class	A
Lighting efficiency class	A
Grease filtering efficiency class	A
Cleaning and care	
Easy-to-clean canopy interior – CleanCover	•
Filter system	
Number of dishwasher-safe stainless steel grease filters (10-ply)	2
Lighting	
Number x W	4 x 3 W
Light intensity in lx	650 lx
Colour temperature in K	3500 Kelvin
Dimmer function	•
Fan	
Dual-action blower	•
Exhaust air	
Air throughput in Level 1 (m ³ /h) according to EN 61591	200
Air throughput in Level 2 (m ³ /h) according to EN 61591	300

DA 2698

Extractor unit

with energy-efficient LED lighting and light-touch switches for easy use.



EAN: 4002516001492 / Material number: 10851400 /
Old Material Number: 28269855GB

Air throughput in Level 3 (m³/h) according to EN 61591	400
Air throughput in Booster level 1 (m³/h) according to EN 61591	640
Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3	36.0
Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3	44.0
Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3	51.0
Sound power in Booster level 1 (dB(A) re 1 pW) acc. to EN 60704-3	62.0
Sound pressure in Level 1 (dB(A) re 20 µPa) according to EN 60704-2-13	22.0
Sound pressure in Level 2 (dB(A) re 20 µPa) according to EN 60704-2-13	30.0
Sound pressure in Level 3 (dB(A) re 20 µPa) according to EN 60704-2-13	37.0
Sound pressure in Booster level 1 (dB(A) re 20 µPa) acc. to EN 60704-2-13	48.0
Recirculation	
Air throughput in Level 1 (m³/h) according to EN 61591	135
Air throughput in Level 2 (m³/h) according to EN 61591	220
Air throughput in Level 3 (m³/h) according to EN 61591	365
Air throughput in Booster level 1 (m³/h) according to EN 61591	535
Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3	47.0
Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3	55.0
Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3	62.0
Sound power in Booster level 1 (dB(A) re 1 pW) acc. to EN 60704-3	74.0
Sound pressure in Level 2 (dB(A) re 20 µPa) according to EN 60704-2-13	41.0
Sound pressure in Level 3 (dB(A) re 20 µPa) according to EN 60704-2-13	48.0
Sound pressure in Booster level 1 (dB(A) re 20 µPa) acc. to EN 60704-2-13	59.0
Sound pressure in Level 1 (dB(A) re 20 µPa) according to EN 60704-2-13	32.0
Safety	
Safety switch-off	•
Technical data	
Canopy width in mm	880
Canopy height in mm	63
Canopy depth in mm	293
Net weight in kg	14.0
Length of supply lead in m	1.5
Standard plug fitted	•
Minimum height above electric hobs in mm	450

DA 2698

Extractor unit

with energy-efficient LED lighting and light-touch switches for easy use.



EAN: 4002516001492 / Material number: 10851400 /
Old Material Number: 28269855GB

Minimum safety distance above gas hobs (max. 12.6 kW
total power, burner $\leq$ 4.5 kW) in mm

650

Number of phases

1

Total rated load in kW

0.09

Voltage in V

230

Fuse rating in A

10

Frequency in Hz

50

Installation notes

Extraction ducting connection at top

•

Extraction ducting connection at rear

•

Diameter of exhaust duct in mm

150

Combination with WiFi-enabled Miele hob

recommended

Accessories included

Non-return flap

•