
54.1 cm, flat hinge















KSZ10020 Bottle Rack Bottle Rack 710020

This built-in combination refrigerator/freezer keeps foods at their freshest, and has NoFrost for automatic defrosting.

- $\sqrt{\mbox{ Fresh Safe}}$ Fridge drawer for flexible storage of your fresh fruit and vegetables.
- $\sqrt{\mbox{ No Frost}}$ No more defrosting your freezer.
- $\sqrt{\ }$ Adjustable Glass Shelves Height adjustable shelves create the space you need for inspiring dishes in your fridge
- $\sqrt{}$ Our safety glass shelves happily shoulder generous loads of delicacies in your fridge
- $\sqrt{\,}$ Individualize your drawers with various loading options to create the optimal fit for frozen goodies

Features

Technical Data

Energy Efficiency Class: F

Average annual energy consumption in kilowatt hour per year (kWh/

a): 277 kWh/annum

Sum of volume of frozen compartments : 67 | Sum of volume of chill compartments: 187 |

Airborne acoustical noise emissions: 39 dB(A) re 1 pW

Airborne acoustical noise emission class: C

Construction type : Built-in Door panel options : Not possible Width of the appliance: 541 mm Depth of the product: 545 mm

Required niche size for installation (HxWxD) : $1775.0 \times 560 \times 550$

mm

Net weight: 63.8 kg Connection rating: 90 W Fuse protection: 13 A Door hinge : Right reversible Voltage: 220-240 V Frequency: 50 Hz

Approval certificates : CE, VDE

Length of electrical supply cord: 230 cm Storage Period in Event of Power Failure (h): 8 h

Number of compressors: 1

Number of independent cooling systems: 1

Interior ventilator: Yes

Reversible Door Hinge : Yes

Number of Adjustable Shelves in fridge compartment (Stck): 3

Shelves for Bottles: No Frost free system: Freezer Installation type: Full-integrated Type of hinge: Flush-folding





N 50, Built-in fridge-freezer with freezer at bottom, 177.2 x 54.1 cm, flat hinge KI7862FF0G

Feature

Functions

• Bright interior LED fridge light

Design features

- LED Electronic control
- FreshSense constant temperature by intelligent sensor technology Constant temperature control by intelligent sensor technology
- Single cooling circuit

Design features

- 4 safety glass shelves in fridge compartment of which 3 are height adjustable
- 4 door bins

Freshness System

• 1 FreshSafe drawer- The ideal place to store your fruit and vegetables safely.

Food freshness system

- Removeable safety glass shelves in freezer
- 3 transparent freezer drawers, 1 bigbox

Dimension and installation

- Dimensions: 177.2 cm H x 54.1 cm W x 54.5 cm D
- Niche Dimensions: 177.5 cm H x 56 cm W x 55 cm D

Key features - Fridge section

- Right hinged door, reversible
- Connection value 90 W
- 220 240 V
- Transportation handles

Key features - Freezer section

- 2 x egg tray, 1 x ice cube tray
- bottle holder in door tray

Country Specific Options

• Based on the results of the standard 24-hour test. Actual consumption depends on usage/position of the appliance.

Design features

Dimension and installation

Additional features

Performance and Consumption

• EU19_EEK_D: F

• Total Volume: 254 l

• Net Fridge Volume : 187 l

• Net Freezer Volume : 67 l

• Freezing capacity 24h : 6 kg

• Annual Energy Consumption: 277 kWh/a

• Climate Class: SN-ST

• EU19_Fast freezer facility_D

• Noise Level: 39 dB, EU19_Noise emission class_D: C

• Temperature rise time : EU19_Temperature rise time_D: 8.5 H



N 50, Built-in fridge-freezer with freezer at bottom, 177.2 x 54.1 cm, flat hinge KI7862FF0G

COOKING PASSION SINCE 1877

Dimensioned drawings measurements in mm min. 40 Front panel Recommended gap dimensions for flat hinges overhang 1039+B-(min.) 1066+B -(max.)-16-19 0-3 2.5 0-1 3 2.5 2-3 0-1 21 3 2-3 22 0 4 3.5 Lower edge of front panel The gap dimensions recommended in the table must be adhered to in order to ensure that appliance doors do not collide with anything when they are opened, and to avoid causing damage to kitchen units. The specified unit door dimensions are valid for a door gap of 4 mm. measurements in mm Air outlet min. 200 cm² max min. 2200 560 recommended min. 550 1772+8 Ventilation space in the base min. 200 cm² measurements in mm 1772 1012

694

702 733

measurements