

iQ300, Wall-mounted cooker hood, 80 cm, clear glass black printed LC87KHM60B



B

LZ10AXL50	Chimney extension 1500 mm
LZ11AKB16	Clean Air Plus odor filter (replacement)
LZ11AKI16	Clean Air Plus recirculation kit
LZ11AKV16	Clean Air Plus recirc. kit (chimless)
LZ11AXC56	Clean Air Plus recirc. kit external
LZ11AXE61	Chimney standard black
LZ31XXB16	Clean Air Plus odor filter (replacement)
LZ00XXP00	Long Life odor filter (replacement)
LZ10AKR00	Long Life recirculation kit (chimless)
LZ10AKS00	Long Life recirculation kit
LZ10AXK50	Chimney extension 1000 mm

Angled extractor hood with outstanding design and high extraction rate for a powerful performance.

- ✓ LED lights: for optimal visibility and ambience while cooking.
- ✓ touchControl: quickly and easily manage the power levels and the LED light

Typology: Wall-mounted
Length electrical supply cord: 130.0 cm
Height of the appliance: 323 mm
Minimum distance above an electric hob: 450 mm
Minimum distance above a gas hob: 650 mm
Weight: 22.1 kg
Control panel: Electronic
Number of speed settings: 3-stages + intensive setting
Maximum output air extraction: 416 m³/h
Boost position output recirculating: 469 m³/h
Maximum output recirculating air: 367 m³/h
Boost position air extraction: 700 m³/h
Maximum Air flow: 416 m³/h
Number of lights: 2
Noise level: 58 dB(A) re 1pW
Diameter of air outlet: 120 / 150 mm
Grease filter material: Washable aluminium
EAN code: 4242003761007
Connection Rating: 263 W
Fuse protection: 10 A
Nominal power: 220-240 V
Frequency: 50; 60 Hz
Plug type: GB plug
Installation type: Wall-mounted

4 242003 761007

iQ300, Wall-mounted cooker hood, 80 cm, clear glass black printed LC87KHM60B

Key performance features:

- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 ø 15 cm:
- max. Normal use 416 m³/h
- Intensive 700 m³/h
- Noise max. Normal Level: Noise, max. speed in normal us: 58 dB dB*

Features

- 3 x power levels plus intensive setting
- 2 x 1.5W LED
- Colour Temperature: 3500 K
- Twin channel high performance fan motor
- Automatic intensive revert (6mins)
- 2 x metal grease filter cassettes
- easy to clean Inner frame
- Installation: wall
- Rim ventilation

Design

- Black glass
- Chimney hood
- touchControl for extractor speeds and light
- Electronic control

Performance/technical information

- Suitable for ducted and re-circulating operation
- In recirculation operation chimless use possible
- For recirculated extraction a recirculating kit or a CleanAir recirculation kit (accessory) is needed
- Installation system: Wall fixing inclined/flat/cube
- Max. extraction rate: 700 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
- Max. normal use: 58 dB(A) re 1 pW
- Intensive: 67 dB(A) re 1 pW
- Power rating: 263 W
- Light Intensity: 90 lux
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 928-1198 x 790 x 499 mm
- Dimensions recirculating, chimney (HxWxD): 988-1258 x 790 x 499 mm
- Dimensions recirculating, chimless (HxWxD): 452 mm x 790 x 499 mm
- Dimensions recirculating with CleanAir module (HxWxD):
- 1118 x 790 x 499 mm - mounting with outer chimney
- 1188-1458 x 790 x 499 mm - mounting with telescopic chimney
- Blower Efficiency Class: B*
- Lighting Efficiency Class: B*

- Grease Filtering Efficiency Class: C*
- Average Energy Consumption: 56.6 kWh/year*

Optional accessories

- Recirculating kit LZ10AXL50

* In accordance with the EU-Regulation No 65/2014

iQ300, Wall-mounted cooker hood, 80 cm, clear glass black printed LC87KHM60B



