

iQ700, Island cooker hood, 90 cm, Stainless steel LF91BUV50B



A+



LZ53451 Standard odor filter (replacement), LZ31XXB16 Clean Air Plus odor filter (replacement), LZ32CBB14 Clean Air Standard odor filter (repl.), LZ00XXP00 Long Life odor filter (replacement), LZ12285 Chimney extension 1100 mm, LZ12310 Adapter for roof inclination left/right, LZ12385 Chimney extension 1600 mm, LZ12410 Adapter for roof inclination front/back, LZ12510 Extension for mounting kit 500 mm, LZ12530 Extension for mounting kit 1000 mm, LZ22CBI14 Clean Air Standard recirculation kit, LZ22CXC56 Clean Air Plus recirc. kit external, LZ22FXD51 Long Life recirculation kit external, LZ53850 Standard recirculation kit

The island hood features a very high extraction rate in a distinguished design that coordinates with a range of Siemens appliances, as well as your kitchen.

- ✓ iQdrive motor - The quiet, high-performance motor ensures efficient removal of odours and steam.
- ✓ cookConnect and climateControl sensor: detects and removes steam and odours automatically
- ✓ voiceControl – Control hood functions and lighting using your voice.
- ✓ Home Connect – The app that makes your hood work smarter.
- ✓ Peace of mind is just a click away - remoteMonitoring.

Typology: Island/Ceilling
 Length electrical supply cord: 130.0 cm
 Height of the chimney: 698-878/698-998 mm
 Height of the appliance: 46 mm
 Minimum distance above an electric hob: 550 mm
 Minimum distance above a gas hob: 650 mm
 Weight: 29.9 kg
 Control panel: Electronic
 Number of speed settings: 3-stage + 2 intensive
 Maximum output air extraction: 598 m³/h
 Boost position output recirculating: 561 m³/h
 Maximum output recirculating air: 462 m³/h
 Boost position air extraction: 981 m³/h
 Maximum Air flow: 598 m³/h
 Number of lights: 4
 Noise level: 62 dB(A) re 1pW
 Diameter of air outlet: 120 / 150 mm
 Grease filter material: Washable stainless steel
 EAN code: 4242003832073
 Connection Rating: 266 W
 Fuse protection: 10 A
 Nominal power: 220-240 V
 Frequency: 50; 60 Hz
 Plug type: GB plug
 Installation type: Island
 Delay Shut off modes: 10 min



iQ700, Island cooker hood, 90 cm, Stainless steel LF91BUV50B

Key performance features:

- Energy Efficiency Class: A+ (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 ø 15 cm:
- max. Normal use: 598 m³/h
- Intensive: 981 m³/h
- Noise max. Normal Level: Noise, max. speed in normal use: 62 dB dB*

Home Connect: Remote Monitoring and Control

- Home Connect: Remote Monitoring and Control for connected home appliances and operation via smartphone or tablet (only in countries where Home Connect service is available)
- The Home Connect functionality can be extended by integrating numerous applications from external cooperation partners (partnerships)
- Voice Control enabled via popular voice assistants (only in countries where this service is available)
- Interval function: available via Home Connect
- Silence function: available via Home Connect

Features

- touchControl with 7-segment display
- 3 power levels and 2 intensive settings
- Automatic intensive revert (6 mins)
- cookConnect hob based hood control
- climateControl sensor
- Fully automatic hood
- softLight with dimmer function
- 4 x 1.5W LED
- Additional noise reduction insulation
- Efficient BLDC motor
- Twin channel high performance fan motor
- Automatic after running (Automatic after running (10 minutes))
- Grease and charcoal filter saturation indicators
- 3 x metal grease filter cassettes - dishwasher safe
- Steel filter cover

Design

- Stainless Steel
- Installation: Ceiling
- Electronic control

Performance/technical information

- Suitable for ducted and re-circulating operation
- For recirculated extraction a recirculating kit or a CleanAir recirculation kit (accessory) is needed
- Max. extraction rate: 981 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
- Max. normal use: 62 dB(A) re 1 pW
- Intensive: 73 dB(A) re 1 pW
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:

- Extraction rate in recirculation mode: Max. normal use: 462 m³/h
- Intensive: 561 m³/h
- Noise level in recirculation mode: Max. normal use: 68 dB(A) re 1 pW
- Intensive: 72 dB(A) re 1 pW
- Power rating: 266 W
- Light Intensity: 411 lux
- Colour Temperature: 3500 K
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 744-924 x 898 x 600 mm
- Dimensions recirculating, chimney (HxWxD): 744-1044 x 898 x 600 mm
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: B*
- Average Energy Consumption: 37.5 kWh/year*

Optional accessories

- Recirculating kit LZ53451

* In accordance with the EU-Regulation No 65/2014

iQ700, Island cooker hood, 90 cm, Stainless steel LF91BUV50B

