

iQ500, Telescopic cooker hood, 90 cm, Stainless steel
LI97SA561B



B

For clean lines the powerful telescopic cooker hood disappears into an upper cabinet, perfect for modern kitchens.

- ✓ iQdrive motor - The quiet, high-performance motor ensures efficient removal of odours and steam.
- ✓ LED lights: for optimal visibility and ambience while cooking.

HZG9AS00S	Adapter
LZ10ITP00	Long Life odor filter (replacement)
LZ11ITD11	Long Life recirculation kit external
LZ11IXB16	Clean Air Plus odor filter (replacement)
LZ11IXC16	Clean Air Plus recirc. kit external
LZ12ITB14	Clean Air Standard odor filter (repl.)
LZ12ITI14	Clean Air Standard recirculation kit
LZ45610	Standard odor filter (replacement)
LZ45650	Standard recirculation kit
LZ49200	Installation kit for 90cm wide wall unit
LZ49601	Lowering frame

Typology:Pull-out
Length electrical supply cord: 175.0 cm
Min. required niche size for installation (HxWxD): 385mm x 524.0mm x 290mm mm
Minimum distance above an electric hob:430 mm
Minimum distance above a gas hob: 650 mm
Weight: 14.5 kg
Control panel:Electronic
Number of speed settings: 3-stage + 2 intensive
Maximum output air extraction:395 m³/h
Boost position output recirculating:628 m³/h
Maximum output recirculating air: 358 m³/h
Boost position air extraction:700 m³/h
Maximum Air flow: 395 m³/h
Number of lights:3
Noise level:53 dB(A) re 1pW
Diameter of air outlet: 120 / 150 mm
Grease filter material: Washable stainless steel
EAN code:4242003880289
Connection Rating: 146 W
Fuse protection:10 A
Nominal power:220-240 V
Frequency:50; 60 Hz
Plug type: GB plug
Installation type: Built-in
Delay Shut off modes: 10 min



iQ500, Telescopic cooker hood, 90 cm, Stainless steel LI97SA561B

Features

- Soft touch button control with 7-segment display
- 3 power levels and 2 intensive settings
- softLight with dimmer function
- 3 x 1,5W LED
- Efficient BLDC motor
- Automatic intensive revert (6mins)
- Automatic after running (Automatic after running (10 minutes))
- 3 x metal grease filter cassettes - dishwasher safe
- Grease and charcoal filter saturation indicators

Design

- 90 cm wide
- Stainless Steel
- Handle strip specification: stainless steel with logo
- Steel filter cover

Performance

- Suitable for ducted and re-circulating operation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 ø 15 cm:
- max. Normal use: 395 m³/h
- Intensive: 700 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 53 dB(A) re 1 pW
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
- Max. normal use: 53 dB(A) re 1 pW
- Intensive: 69 dB(A) re 1 pW
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:
- Extraction rate in recirculation mode: Max. normal use: 358 m³/h
- Intensive: 628 m³/h
- Noise level in recirculation mode: Max. normal use: 60 dB(A) re 1 pW
- Intensive: 71 dB(A) re 1 pW
- Colour Temperature: 3500 K
- Light Intensity: 355 lux
- Power rating: 146 W
- Average Energy Consumption: 38.8 kWh/year*
- Blower Efficiency Class: B*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: B*

Planning and installation information

- Installation system: Telescopic comfort installat.
- Dimensions (HxWxD): 426 x 898 x 290 mm
- Built-in dimensions (HxWxD): 385 x 524 x 290 mm
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)

- Electrical cable length 1.75 m

* In accordance with the EU-Regulation No 65/2014

iQ500, Telescopic cooker hood, 90
cm, Stainless steel
LI97SA561B



