

# Series 4, Built-under double oven NBS533BS0B





HEZ631070 Baking tray, enamelled, HEZ632070 Multipurpose pan, enamelled, HEZ634000 Baking and roasting grid, HEZ636000 Glass pan, HEZ638000 Full ext rails, level independent, HEZ664000 Baking and roasting grid, steam, HEZ915003 Glass roasting dish, 5,4 L, HEZ532010 Universal pan, non-stick ceramic coated, HEZ538000 1fold telescopic rail, level independent, HEZ617000 Pizza pan, enamelled, HEZ629070 Air Fry & Grill tray, HEZ327000 Pizza stone, HEZ32WA00 Wireless food thermometer, HEZ530000 Half tray, HEZ531010 Baking tray, non-stick ceramic coated

# The built-in double compact oven with 3D hot air: achieve perfect baking and roasting results on multiple levels simultaneously.

- Red LED display control: easy-to-use thanks to the time functions.
- **Pop-out controls**: Make the front of the oven easy to clean and give it a sleek look.
- EcoClean Direct: less cleaning effort thanks to a special coating which covers the rear wall of the lower oven.
- 2 universal pans, slim size: optimized for smaller amounts of different dishes.

Built-in / Free-standing:	Built-in
Integrated Cleaning system:	Na
Dimensions:	717x594x550 mm
Dimensions of the packed product (HxWxD): 790	) x 660 x 695 mm
Control Panel Material:	Stainless steel
Door Material:	Glass
Net weight:	47.6 kg
Usable volume of cavity:	47
Cooking method: Full width grill, Hotair gentle, Hot	Air, Conventional
heat, Hot air grilling	
Oven control:	mechanical
Number of interior lights:	1
EAN code:	.4242005034628
Energy efficiency rating:	А
Energy consumption per cycle conventional (2010/3	0/EC):0.84
kWh/cycle	
Energy consumption per cycle forced air convection	(2010/30/EC):71
kWh/cycle	
Energy efficiency class (2010/30/EC) - cavity 2:	B
Energy consumption per cycle conventional - cavity 2	2 (2010/30/E <b>C.)</b> 83
kWh/cycle	
Energy efficiency index (2010/30/EC):	94.7 %
Energy efficiency index cavity 2 (2010/30/EC):	
Connection rating:	5300 W
Fuse protection:	25 A
Voltage:	220-240 V
Frequency:	50 Hz
Plug type:no plug (electrical connection by e	lectrician), fixed
connection (electrical connection by electrician)	
Included accessories cavity 1: 2 x combination g	rid, 1 x universal
pan, 2 x Universal pan, slim size	





Series 4, Built-under double oven NBS533BS0B

The built-in double compact oven with 3D hot air: achieve perfect baking and roasting results on multiple levels simultaneously.

#### Design

- LED-Display Control (Red)
- Interior halogen light
- Rotary dial, Retractable control dials, round

#### Features

- Control panel lock
- Electronic clock timer
- Automatic start
- Heating-up indicator

#### Top oven additional features

- Cavity volume: 34 litre capacity
- Full glass inner door
- Cavity (inner surface) top: Enamel grey
- Door hinge small cavity: Drop down oven door
- 3 shelf positions

#### Main oven additional features

- Cavity volume: 47 litre capacity
- EcoClean Direct : back panel
- Full glass inner door
- Door hinge big cavity: Drop down door

#### Top oven

- Oven with 3 heating methods: conventional top/bottom heat, Large-area grill, Small area grill
- Temperature range 50 °C 275 °C

#### Main oven

- Oven with 5 heating methods: 3D Hotair, conventional top and
- bottom heat, Hotair grilling, full width variable grill, Hotair gentle
- Temperature range 50 °C 275 °C
- Fast pre-heating function

#### Accessories

- 2 x combination grid, 1 x universal pan, 2 x Universal pan, slim size


#### Performance/technical information

- Energy efficiency rating (acc. EU Nr. 65/2014): B(at a range of energy efficiency classes from A+++ to D)
- Energy consumption per cycle in conventional mode:0.83 kwh
- Number of cavities: Top Cavity Heat source: electrical
- Energy efficiency rating (acc. EU Nr. 65/2014): B(at a range of energy efficiency classes from A+++ to D)
- Energy consumption per cycle in conventional mode:0.83 kWh
- Energy consumption per cycle in fan-forced convection mode:0.71 kwh
- Number of cavities: Main Cavity Heat source: electrical
- Total connected load electric: 5.3 KW
- Nominal voltage: 220 240 V
- Appliance dimension (hxwxd): 717 mm x 594 mm x 550 mm


- Please refer to the dimensions provided in the installation manual



# Series 4, Built-under double oven NBS533BS0B




## measurements in mm



	fitted	flush
Induction hob	39	40
Full-surface induction hob	49	50
Gas hob	29	40
Electric hob	29	32

If the appliance will be installed underneath a hob, the following worktop thicknesses (including substructure if necessary) must

min. worktop thickness



A: Recessed depth 29-50 mm. See hob dimensional drawing. B: Min. distance: Induction hob: 5 mm Gas hob: 5 mm Electric hob: 2 mm

### measurements in mm

measurements in mm

be taken into account.

