# N 70, Gas hob, 60 cm, Stainless steel T26CIH8N0





# Optional accessories

Z2471X0 Wok ringZ9404SE0 4 pieces SetZ9406SE0 6 pieces Set

The gas hob with precise flame control, removable dials and pan supports that are suitable for dishwashers - for Comfort Clean.

- $\sqrt{\mbox{ FlameSelect}^{\mbox{\scriptsize (B)}}}$  : Gain precise control of your flame.
- $\sqrt{\ }$  Metallic Sword Dial: Precise and removable for easy cleaning.
- $\sqrt{\phantom{}}$  Cast Iron Pan Supports: For maximum stability and dishwasher cleaning.
- $\sqrt{\mbox{ Wok Burner: Powerful cooking at up to 3.5 kW.}}$
- $\sqrt{\ }$  Gas Safety Cut-Off: Safety first! No flame, no gas flow.

#### Features

#### Technical Data

Product name/family : gas hob w integrated controls

Built-in / Free-standing : Built-in

Energy input : Gas

Total number of positions that can be used at the same time : 4 Required niche size for installation (HxWxD) :  $45 \times 560-562 \times 10^{-2}$ 

480-492 mm

Width of the appliance : 582 mm Dimensions : 51.5x582x520 mm

Dimensions of the packed product (HxWxD) : 141 x 651 x 578 mm

Net weight: 10.8 kg Gross weight: 12.0 kg

Residual heat indicator: without Location of control panel: Front Basic surface material: Stainless steel Color of surface: Stainless steel Length electrical supply cord: 100.0 cm EAN code: 4242004284536

Gas connection rating : 8000 W Fuse protection : 3 A

Fuse protection : 3 A Voltage : 220-240 V Frequency : 50; 60 Hz





#### Features

#### Design

- Stainless steel surface
- black cast iron pan supports with protective rubber feet
- full metal

### Usage convenience

- FlameSelect with 9 steps: precisely control and adjust the flame in pine defined levels
- Design co-ordinated control dials, front: easily access dials in front with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame

## Burners and power

- 4 burner hob
- Left front: Standard burner up to 1.75 KW (depending on gas type)
- Left rear: Standard burner up to 1.75 KW (depending on gas type)
- Right rear: WOK burner up to 3.5 KW (depending on gas type)
- Right front: Economy burner up to 1 KW (depending on gas type)

# Cleaning

- Removable control dials for easy cleaning between knobs.
- Dishwasher suitable pan supports for easy cleaning.

# Safety

• Flame failure safety device: prevents unwanted gas flow when flame goes out.

## Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE)
  NG H/E 20mbar, E+ 20/25mbar Natural gas H 25 mbar (HU)
  Natural gas L 25 mbar (NL) Liquid gas G30,31 28-30/37mbar
  Liquid gas G30 37 mbar (PL) Liquid gas 50 mbar
- Factory set for connection to mains gas
- Nozzle set for LPG jets (28-30/37mbar) included. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm): 51.5 x 582 x 520
- Required niche size for installation (HxWxD mm): 45 x 560 x (480 492)
- Min. worktop thickness: 30 mm
- Power cord: 1 m
- Connected load: 8 KW



